

TECHNICAL DATA SHEET

Material: Recycled Black Injection Grade Impact Modified PP Copolymer

Reference: A-85V

Attributes:

- Medium flow impact modified copolymer PP
- Exceptional ductility and impact properties
- Widely used in automotive applications

Packaging:

| | |
|----------------------------|-------------------|
| A085V - 25kg Paper Sacks | A385V - Octaboxes |
| A185V - 25kg Plastic Sacks | A485V - Tanker |
| A285V - Bulk Bags | |

Typical Values

| Property | Test Method | Units | Average | Range |
|------------------------------|--------------------------|-------------------|---------|---------|
| Melt Flow Index | ISO 1133 - 230°C, 2.16kg | g/600secs | 12.50 | 10 - 15 |
| Moisture | Internal | % | - | < 0.1 |
| Notched IZOD Impact Strength | ISO 180/1A, 23C | kJ/m ² | - | > 19 |

LRS1413 - 0

Date Printed: 21/07/2011

Date Created: 21/07/2011

This information is offered in good faith and meant only as a guide. The transformer or user will be, in each case, responsible for the processing conditions and the final use of the product. Freedom under patents, copyright and registered designed cannot be assumed.

REGISTERED OFFICE: Allerton Bywater Business Park, Newton Lane, Allerton Bywater, Castleford, West Yorkshire, WF10 2AL

REGISTERED No: 07289595 - ENGLAND