

# TECHNICAL DATA SHEET

**Material:** Recycled Black Extrusion Grade HDPE Compound

**Reference:** H-450

**Attributes:**

- Even and consistent appearance
- Suitable for Blow Mould & Pipe Extrusion applications
- Good ease of moulding

**Packaging:**

H0450 - 25kg Paper Sacks	H3450 - Octaboxes
H1450 - 25kg Plastic Sacks	H4450 - Tanker
H2450 - Bulk Bags	

## Typical Values

Property	Test Method	Units	Average	Range
Density	ISO 1872/1 - 1986	kg/m <sup>3</sup>	0.96	0.950 - 0.970
Melt Flow Index	ISO 1133 - 190°C, 2.16kg	g/600secs	0.35	.2 - .5
Moisture	Internal	%	-	< 0.1
Notched IZOD Impact Strength	ISO 180/1A, 23C	kJ/m <sup>2</sup>	-	> 5

LRS1418 - 0

Date Printed: 21/07/2011

Date Created: 21/07/2011

This information is offered in good faith and meant only as a guide. The transformer or user will be, in each case, responsible for the processing conditions and the final use of the product. Freedom under patents, copyright and registered designed cannot be assumed.

REGISTERED OFFICE: Allerton Bywater Business Park, Newton Lane, Allerton Bywater, Castleford, West Yorkshire, WF10 2AL

REGISTERED No: 07289595 - ENGLAND